



### **PRODUCT DESCRIPTION**

**INDALOBLANC® FIX 3** is intended for application on all types of greenhouse covers (plastic, glass, ...). It is a water-soluble liquid product based on selected aggregates and additives. By lowering the incident solar radiation, it also contributes to changing the climate within the greenhouse.

The following environmental factors are controlled by **INDALOBLANC® FIX 3**:

- Radiation.
- Temperature.
- Humidity.

**INDALOBLANC® FIX 3** has a good adhesion and deformability on the cover of the greenhouse; at the same time it has a good covering power.

### **CHARACTERISTICS AND APPLICATIONS**

- Liquid product of easy dissolution in water.
- Good adhesion.
- Good deformability.
- Good covering power.
- High power of reflection.
- Low sedimentation during its application.
- Stable product in a wide range of doses in water to obtain different shade intensities.
- Approximate duration between 2 and 3 months, depending on the weather conditions.

### **HOW TO USE**

**INDALOBLANC® FIX 3** is applied on the cover of the greenhouse.

To obtain the best results with **INDALOBLANC® FIX 3** it is necessary to follow the following steps:

- The product will be mixed in its original bucket with a mixer at low revolutions until the suitable homogeneity is obtained.
- Pour the product into the clean water tank. The water must be free of any physical and chemical contamination.
- With the help of some suitable mixers dilute the product in the water.
- It is important to have a system of suitable mixers to guarantee the total dilution of **INDALOBLANC® FIX 3**.
- Maintain the continuous agitation of the mixers during the entire period of application of the product.

Shade intensity				
Mixing water	High	Medium	Low	Very Low
Product	20 L	20 L	20 L	20 L
Water	60 L	80 L	100 L	200 L
Approximate duration: 2-3 months				

\*Example: For a medium intensity one bucket of **INDALOBLANC® FIX 3** (20 L) and four buckets of water (80 L) would be need.

### **RECOMMENDATIONS AND PRECAUTIONS**

- Do not apply with risk of frost, rain and strong winds.
- It should not be mixed with other products.
- For a correct adhesion the cover must be free of dust, grease or previous whitening products.
- Do not apply on wet covers.
- The persistence of the product depends on different variables beyond our reach such as peak seasonal rainfalls, hail, strong winds, age of plastic and / or inadequate cleaning of the cover.
- It is recommended to clean the equipment used in the application with clean water.
- Use of **INDALOBLANC® CLEAN** is advised if the product needs to be removed from the greenhouse cover.

### **COMMERCIAL FORMATS**

**INDALOBLANC® FIX 3** comes in 24 kg buckets (20 L).

NOTE: The directions for usage are provided based on our testing and knowledge and they are not intended to imply any commitment on the part of INDALOBLANC S.L. They also do not exempt the consumer from inspecting and verifying the goods to ensure that they are being used correctly. For proper traceability, any claims must be accompanied by the original packaging.

INDALOBLANC S.L. disclaims any responsibility for how their products are used by the parties engaged in the application and restricts its liability to any potential damages that can be directly and solely attributed to defects in the supplied products' manufacturing.