

PRODUCT DESCRIPTION



INDALOBLANC® FLEX is a bleaching product for greenhouses formulated with selected aggregates and additives, designed to control the internal climate of the greenhouse. It provides an even coverage that helps maintain a constant temperature, reducing thermal stress on crops during periods of high solar radiation.

It is intended for application on greenhouse covers. Its formulation allows for easy application by spraying, ensuring a homogeneous distribution.

INDALOBLANC® FLEX helps control the following climatic parameters:

- Helps regulate the internal temperature of the greenhouse.
- Reflects infrared (IR) and ultraviolet (UV) rays, reducing excess heat.
- Allows the passage of PAR radiation, essential for photosynthesis and the proper development of crops.
- Contributes to a more stable microclimate, improving agricultural performance.
- Reduces the risk of burns and thermal stress on plants.

FEATURES AND APPLICATIONS

- Powder product that dissolves easily in water.
- Good adherence to all types of greenhouse covers.
- High deformability.
- High reflective power.
- Excellent coverage power.
- Low sedimentation during application.
- Ideal product for application on greenhouse covers from March to July.
- Approximate duration of **2 to 3 months**, depending on weather conditions.
- Very fine product that protects bleaching pumps.
- Non-aggressive towards wire or plastic.
- Free of heavy metals (chromium and bromine free).

RECOMMENDED USAGE

Recommended Dose

25kg/100L water

Approximate yield for 1000 m²

Note: Yield may vary depending on the application method, type of surface, and dilution used. Using a lower dose may reduce the durability of the product on the greenhouse cover.

For best results with **INDALOBLANC FLEX**, follow these steps:

- Slowly dilute the product in clean water until a homogeneous mixture is achieved, preferably performing a pre-dilution.
- It is essential to have a proper agitation system and maintain continuous agitation throughout the application process.
- It is recommended to clean the equipment used for application with clean water.
- To remove the product, use **INDALOBLANC® CLEAN** to efficiently eliminate any residue.

PRECAUTIONS

- Do not apply when there is a risk of frost, rain, or strong winds.
- Do not mix with other products.
- For proper adhesion, the cover must be free of dust, grease, or previous bleaching products.
- Do not apply on wet covers.
- The duration of the product depends on various external factors, such as maximum rainfall, hailstorms, strong winds, plastic lifespan, and/or improper cleaning of the cover.

STABILITY

INDALOBLANC® FLEX remains stable under proper storage conditions for 24 months. After that period, it may still be usable, but it may have lost some of its properties.

COMMERCIAL FORMATS

INDALOBLANC® FLEX is palletized in 48-unit pallets of 25 kg each (sales unit: kg).



Note: the instructions for use are made according to our tests and knowledge. They do not release the consumer from the examination and verification of the products for its correct use. The responsibility of the company will be limited to the value of the merchandise used. Claims must be accompanied by the original packaging to allow proper traceability.

INDALOBLANC is not responsible, in any case, for the use of its products by the parties involved in the application, limiting INDALOBLANC's liability exclusively to possible damages directly and exclusively attributable to the products supplied due to manufacturing failures.