

PRODUCT DESCRIPTION



INDALOBLANC® BLANCO ESPAÑA is a bleaching product for greenhouses formulated with selected aggregates. It is designed for controlling the internal climate of the greenhouse. It provides an even coverage that helps maintain a constant temperature, reducing thermal stress on crops during periods of high solar radiation.

Intended for application on greenhouse covers.

FEATURES AND APPLICATIONS

- | | |
|--|--|
| <ul style="list-style-type: none"> • Powder product that dissolves easily in water. • Ideal product for application on the greenhouse cover throughout the entire crop cycle. • Non-aggressive towards wire or plastic. | <ul style="list-style-type: none"> • Free of heavy metals (chromium and bromine free). • No adhesive properties. • Its function is limited to shading during its time on the cover. • Very fine product that protects bleaching pumps. |
|--|--|

RECOMMENDED USAGE

Recommended Dose		
Low	Medium	High
20kg/100L water	40kg/100L water	60kg/100L water
Approximate yield for 1000 m ²		

Note: Yield may vary depending on the application method, type of surface, and dilution used. Using a lower dose may reduce the durability of the product on the greenhouse cover.

For best results with **INDALOBLANC BLANCO ESPAÑA**, follow these steps:

- Slowly dilute the product in clean water until a homogeneous mixture is achieved, preferably performing a pre-dilution.
- It is essential to have a proper agitation system and maintain continuous agitation throughout the application process.
- It is recommended to clean the equipment used for application with clean water.

PRECAUTIONS

- | | |
|---|--|
| <ul style="list-style-type: none"> • Do not apply when there is a risk of frost, rain, or strong winds. • Do not mix with other products. • For proper adhesion, the cover must be free of dust, grease, or previous bleaching products. | <ul style="list-style-type: none"> • Do not apply on wet covers. • The duration of the product depends on various external factors, such as maximum rainfall, hailstorms, strong winds, plastic lifespan, and/or improper cleaning of the cover. |
|---|--|

STABILITY

INDALOBLANC® BLANCO ESPAÑA remains stable under proper storage conditions for 24 months. After that period, it may still be usable, but it may have lost some of its properties.

COMMERCIAL FORMATS

INDALOBLANC® BLANCO ESPAÑA is palletized in 60-unit pallets of 20 kg each (sales unit: kg).

Note: the instructions for use are made according to our tests and knowledge. They do not release the consumer from the examination and verification of the products for its correct use. The responsibility of the company will be limited to the value of the merchandise used. Claims must be accompanied by the original packaging to allow proper traceability.

INDALOBLANC is not responsible, in any case, for the use of its products by the parties involved in the application, limiting INDALOBLANC's liability exclusively to possible damages directly and exclusively attributable to the products supplied due to manufacturing failures.